





Plastic Modular Belt


Series uni Flex L-ASB




uni Flex L-ASB R1.6
Surface Opening: 50%




uni Flex L-ASB R2.2
Surface Opening: 47%




Sideflexing belt
Nominal pitch: 50.8 mm (2.00 in)
Surface type: Flat
Surface opening: 47%/50%
Backflex radius: 100.0 mm (3.94 in)
Pin diameter: 6 mm (0.24 in)
Min. inside radius: R1.6 x belt width, R2.2 x belt width





uni Flex L-ASB Rubber Top R2.2



uni Flex L-ASB R2.2 Rubber Top: Indent min. 71.0 mm (2.80 in) and Increment 25.4 mm (1.00)
uni Flex L-ASB R1.6 Rubber Top: Indent min. 97.0 mm (3.82 in) and Increment 25.4 mm (1.00 in).



uni Flex L-ASB Tab R2.2
Surface Opening: 50%



Type	Belt materials and colors	Pin materials and colors		mm	in		mm	in
uni Flex L-ASB R2.2 uni Flex L-ASB Tab R2.2 uni Flex L-ASB R1.6	POM-D B W	PA6.6 B	P (Nominal)	50.8	2.00	W	325.9	12.83
	PP B W		S	11.0	0.43	X	3.0	0.12
uni Flex L-ASB Rubber Top R2.2 uni Flex L-ASB Rubber Top Tab R2.2 uni Flex L-ASB Rubber Top R1.6	PP B + 03 K		T	15.0	0.59	Y	9.0	0.35
			V	306.5	12.07	Z	14.0	0.55

Non standard material and color: See uni Material and Color Overview.

Alternative pin and lock materials:

Snap Pin A1: PP **W** PBT **LG** PA6.6 **B**

Lockpin: PBT **LG**

uni Flex L-ASB 47% R1.6

Belt width		Permissible tensile force (Belt/pin material)								Belt weight (Belt/pin material)				*Min. No. drive sprocket per shaft	Number of wear strips (Min. No.)	
		POM-D/PA6.6				PP/PA6.6				POM-D/PA6.6		PP/PA6.6			**Carry (pcs)	**Return (pcs)
mm	in	N	lbf	N	lbf	N	lbf	N	lbf	kg/m	lb/ft	kg/m	lb/ft			
250	9.8	10000	2248	2440	549	5000	1124	1440	324	2.5	1.65	1.5	1.01	2	2	2
326	12.8	13040	2931	2440	549	6520	1466	1440	324	3.2	2.15	2.0	1.31	3	3	2
403	15.9	16120	3624	3110	699	8060	1812	1960	441	3.9	2.65	2.4	1.63	3	3	2
479	18.9	19160	4307	3110	699	9580	2154	1960	441	4.7	3.15	2.9	1.93	5	4	2
555	21.9	22200	4991	3110	699	11100	2495	1960	441	5.4	3.66	3.3	2.24	5	4	2
631	24.8	25240	5674	3110	699	12620	2837	1960	441	6.2	4.16	3.8	2.54	5	5	3
708	27.9	28320	6366	3110	699	14160	3183	1960	441	6.9	4.66	4.2	2.85	5	5	3
784	30.9	31360	7050	3110	699	15680	3525	1960	441	7.7	5.16	4.7	3.16	7	6	3
860	33.9	34400	7733	3110	699	17200	3867	1960	441	8.4	5.66	5.2	3.47	7	6	3
936	36.9	37440	8417	3110	699	18720	4208	1960	441	9.2	6.16	5.6	3.77	7	7	4
1013	39.9	40520	9109	3110	699	20260	4554	1960	441	9.9	6.67	6.1	4.08	7	7	4

Additional non-standard belt widths are available in steps of 25.4 mm (1.00 in).
General belt tolerance is +0/-0.4% at 23°C/73°F. For exact belt width contact Customer Service. Non standard belt width on request.
*Max. Load per Drive Sprocket. Belt material: POM-D 2500 N (562 lbf), PP 1200 N (270 lbf).
**Max. Spacing between wear strips, Carry: 152 mm (6 in); Return: 304 mm (12 in).

 = Single Link

uni Flex L-ASB 47% R2.2

Belt width		Permissible tensile force (Belt/pin material)								Belt weight (Belt/pin material)				*Min. No. drive sprocket per shaft	Number of wear strips (Min. No.)	
		POM-D/PA6.6				PP/PA6.6				POM-D/PA6.6		PP/PA6.6			**Carry (pcs)	**Return (pcs)
mm	in	N	lbf	N	lbf	N	lbf	N	lbf	kg/m	lb/ft	kg/m	lb/ft			
250	9.8	10000	2248	2440	549	5000	1124	1440	324	2.5	1.65	1.5	1.01	2	2	2
326	12.8	13040	2931	2440	549	6520	1466	1440	324	3.2	2.15	2.0	1.31	3	3	2
403	15.9	16120	3624	3110	699	8060	1812	1960	441	3.9	2.65	2.4	1.63	3	3	2
479	18.9	19160	4307	3110	699	9580	2154	1960	441	4.7	3.15	2.9	1.93	5	4	2
555	21.9	22200	4991	3110	699	11100	2495	1960	441	5.4	3.66	3.3	2.24	5	4	2
631	24.8	25240	5674	3110	699	12620	2837	1960	441	6.2	4.16	3.8	2.54	5	5	3
708	27.9	28320	6366	3110	699	14160	3183	1960	441	6.9	4.66	4.2	2.85	5	5	3
784	30.9	31360	7050	3110	699	15680	3525	1960	441	7.7	5.16	4.7	3.16	7	6	3
860	33.9	34400	7733	3110	699	17200	3867	1960	441	8.4	5.66	5.2	3.47	7	6	3
936	36.9	37440	8417	3110	699	18720	4208	1960	441	9.2	6.16	5.6	3.77	7	7	4
1013	39.9	40520	9109	3110	699	20260	4554	1960	441	9.9	6.67	6.1	4.08	7	7	4
1089	42.9	43560	9792	3110	699	21780	4896	1960	441	10.7	7.17	6.5	4.39	9	8	4

Additional standard belt widths are available in steps of 76.2 mm (3.00 in) Additional non-standard belt widths are available in steps of 25.4 mm (1.00 in)

1699	66.9	67960	15277	3110	699	33980	7639	1960	441	16.7	11.19	10.2	6.85	13	12	6
------	------	-------	-------	------	-----	-------	------	------	-----	------	-------	------	------	----	----	---


Additional standard belt widths are available in steps of 76.2 mm (3.00 in) Additional non-standard belt widths are available in steps of 25.4 mm (1.00 in)

1927	75.9	77080	17328	3110	699	38540	8664	1960	441	18.9	12.69	11.6	7.77	13	13	7
------	------	-------	-------	------	-----	-------	------	------	-----	------	-------	------	------	----	----	---

General belt tolerance is +0/-0.4% at 23°C/73°F. For exact belt width contact Customer Service. Non standard belt width on request.
*Max. Load per Drive Sprocket. Belt material: POM-D 2500 N (562 lbf), PP 1200 N (270 lbf).
**Max. Spacing between wear strips, Carry: 152 mm (6 in); Return: 304 mm (12 in).

 = Single Link

Design Guidelines




	uni Flex L-ASB R2.2 uni Flex L-ASB Tab R2.2	uni Flex L-ASB R1.6 (inside)
A	min. 1.5 x W	min. 1.5 x W
B	min. 3.2 x W	min. 2.6 x W
C	min. 2.2 x W	min. 1.6 x W
D	min. 2.0 x W	min. 2.0 x W
E	min. 2.0 x W	min. 2.0 x W
F	min. 8.9 x W	min. 7.7 x W
G	min. 8.4 x W	min. 7.2 x W


uni Flex L-ASB R1.6 can not be used in S-conveyors.

Accessories

Side Guard



Side Guard Airflow





Type	Side Guard Material & color	H	
		mm	in
Side Guard	POM-D B W	10.0	0.39
		25.4	1.00
		50.0	1.97
Side Guard Airflow		50.0	1.97

* Min. indent for Side Guard is: 80.0 mm (3.15 in) and Increment 25.4 mm (1.00 in)
Non Standard material and color: See uni Material and Color Overview.


Accessories

AmFlight



Type	Material & color	H	H ¹		H ²	
			mm	in	mm	in
AmFlight	PE W	H > H ¹	25.4	1.00	26.0	1.02

Other Non Standard option: See uni AmFlight Overview.



	mm	in
A min	83.0	3.27
B	33.0	1.30
PI min	68.5	2.70

Increment: 25.4 mm (1.00 in)


Sprocket

No. of teeth	Bore size												Overall diameter		Pitch diameter		Hub diameter		Dimension A		Dimension B		Single row/Two way	Double row/Two way	Molded	Machined	
	Pilot Bore	in	0.75	0.79	0.98	1.00	1.18	1.25	1.50	1.57	2.36	2.50															3.54
	mm	19.1	20.0	25.0	25.4	30.0	31.8	38.1	40.0	60.0	63.5	90.0	mm	in	mm	in	mm	in	mm	in							
Z08	x				●	●				●				134.6	5.30	131.5	5.18	107.6	4.23	54.4	2.14	74.9	2.95	x			x
Z10	x				●	●	●			●				168.3	6.63	164.0	6.46	141.3	5.56	71.4	2.81	90.8	3.57	x			x
Z12	x				●		●	●	●	●		■		203.5	8.01	196.5	7.74	176.5	6.94	88.2	3.47	106.8	4.20	x			x
Z15	x				●		●	●	●	●		■		253.4	9.98	245.4	9.66	226.4	8.91	113.2	4.46	131.0	5.16	x			x

Machined sprocket



Machined sprocket



Other sprocket sizes are available upon request
Two-part sprocket are available upon request
Other bore sizes are available upon request
uni Retainer Rings: See uni Retainer Ring data sheet
Width of tooth = 15.0 mm (0.59 in)
Width of sprocket = 30.0 mm (1.18 in)

Max. load per sprocket shown does not take bore size into account.
Please also ensure that sufficient size shaft is chosen for corresponding load.

For correct sprocket position: See uni Assembly Instructions for uni Flex L-ASB.
For more detailed sprocket information, contact Customer Service.

Non standard material and color: See uni Material and Color Overview.



Conveyor Belts




Seamless Belts



Modular Belts



Timing Belts



Transmission Belts



Fabrication & service

Expert advice, quality solutions and local service for all your belting needs
www.ammeraalbeltech.com

Ammeraal Beltech Modular A/S
Hjulumagervej 21
DK-7100 Vejle

T +45 7572 3100
F +45 7572 3348
admin@unichains.com
www.unichains.com

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.