

Belt : P3330 MRTx1/32

Construction

Top Cover

Material :	SBR
Color :	Black
Profile :	MRT
Thickness :	0,08
Hardness - ShA :	70

Bottom Cover

Material :	SBR
Color :	Black
Profile :	Smooth
Thickness :	0,03
Hardness - ShA :	70

Plies / Weaving

Number of plies :	3
Fabric Material :	Nylon
Lateral Rigidity (Weft) :	Flexible
Internal Material :	SBR

Working Characteristics

Overall Thickness :	0,25
Working Load - lbs/in :	330


Overall Weight - lbs/ft ² :	1,5
% Of Elongation :	1

Working Temperature (°F) :	-25 / 225
----------------------------	-----------

Coefficient of friction - Bottom

-On Steel	0,5
-On Plastic	0,45
-On Rollers	0,05

Minimum Diameter (F)	3"
Minimum Diameter (C)	3"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing	20
Clipper® Lacing	3
Ready Set™ Fasteners	187

Bolt Hinged Fasteners	375
Rivet Hinged Fasteners	2

Recommended Joint : Endless

Hot Splice	N/R
Cooking Temperature (°F)	On Demand
Pressure (lbs)	On Demand

Cold Splice	ESD
Glue To Use	On Demand

Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----