


Belt : P3330 Vx1/32

Construction



Top Cover

Material : SBR
Color : Black
Profile : VT
Thickness : 0,28
Hardness - ShA : 70



Bottom Cover

Material : SBR
Color : Black
Profile : Smooth
Thickness : 0,03
Hardness - ShA : 70

Plies / Weaving

Number of plies : 3
Fabric Material : Nylon
Lateral Rigidity (Weft) : Flexible
Internal Material : SBR

Working Characteristics

Overall Thickness : 0,47
Working Load - lbs/in : 330


Overall Weight - lbs/ft² : 2
% Of Elongation : 1

Working Temperature (°F) : -25 / 225

Coefficient of friction - Bottom

-On Steel : 0,5
-On Plastic : 0,45
-On Rollers : 0,05

Minimum Diameter (F) : 3"
Minimum Diameter (C) : 3"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 20
Clipper® Lacing : 3
Ready Set™ Fasteners : 187

Bolt Hinged Fasteners : 375
Rivet Hinged Fasteners : 2

Recommended Joint : Endless

Hot Splice : N/R
Cooking Temperature (°F) : On Demand
Pressure (lbs) : On Demand

Cold Splice : ESD
Glue To Use : On Demand

Other Specifications

FDA : No Antistatic : No Antimicrobial : No